

ZIDNI MODEL DC Inverter Serija

Wi-Fi kao standard



Model	AZI-WO25VD		AZI-WO35VD		AZI-WO50VD	
Funkcija	Hlađenje/Grijanje		Hlađenje/Grijanje		Hlađenje/Grijanje	
Kapacitet	Hlađenje	kW	2,50 (0,60-2,80)	3,20 (0,60-3,60)	4,60 (0,65-5,20)	
	Grijanje	kW	2,75 (0,60-3,00)	3,56 (0,60-3,80)	5,10 (0,70-5,30)	
Pdesignh (-10°C)	kW		2,50	3,20	3,40	
SEER / SCOP	6,10 / 4,00		6,10 / 4,00	6,10 / 4,00	6,10 / 4,20	
Energetska klasa hlađenje/grijanje	A++ / A+		A++ / A+	A++ / A+	A++ / A+	
Napajanje	Ph, V, Hz		1, 220-240, 50	1, 220-240, 50	1, 220-240, 50	
Apsorbirana snaga	Hlađenje	W	800 (120-1300)	1020 (120-1400)	1430 (150-1750)	
	Grijanje	W	780 (120-1400)	1040 (120-1500)	1410 (160-1680)	
Jakost struje	Hlađenje	A	6,70	7,20	8,00	
	Grijanje	A	7,20	7,70	8,00	
Količina zraka	Unutarnja	m³/h	500-400-300-250	500-400-300-250	850-780-650-550	

Unutarnja jedinica

Razina zvučnog tlaka	dB (A)	38-34-31-28	39-34-31-28	45-42-37-33	
Razina zvučne snage	dB (A)	50-46-43-40	51-47-43-40	58-53-50-45	
Dimenzije uređaja	Š x V x D	mm	794x264x182	794x264x182	945x298x211
Neto masa / Bruto masa	kg	8,5 / 10,0	8,5 / 10,0	12,0 / 15,0	

Vanjska jedinica

Razina zvučnog tlaka		dB (A)	50	52	54
Razina zvučne snage		dB (A)	60	62	64
Priključak cjevovoda	Plin	mm	Ø9,52	Ø9,52	Ø9,52
	Tekućina	mm	Ø6,35	Ø6,35	Ø6,35
Dimenzije uređaja		Š x V x D	mm	776x540x320	848x596x320
Neto masa / Bruto masa		kg	27,0 / 29,5	30,0 / 33,0	33,0 / 36,0
Maksimalna duljina instalacije		m	15	20	20
Maksimalna visinska razlika		m	10	10	10
Standardno područje djelovanja	Hlađenje	°C	-15 ~ +43	-15 ~ +43	-15 ~ +43
	Grijanje	°C	-15 ~ +24	-15 ~ +24	-15 ~ +24

Ova jedinica modernog, kompaktnog dizajna s elegantnim LED zaslonom za prikaz zadane temperature, idealna je nadopuna svim tipovima stambenih i uredskih prostora. Jedinica posjeduje I-Feel mini senzor koji se nalazi u bežičnom upravljaču te dolazi s integriranim Wi-Fi sučeljem za upravljanje putem interneta, kako bi osigurala maksimalnu udobnost i prilagodbu Vašim potrebama.



Bežični
daljinski
upravljač

										
-15°C Hlađenje	I Feel	Ugodan noćni način rada	Inteligentno predzagrijavanje	LED zaslon	Timer	Inteligentno odmrzavanje	Automatsko čišćenje	Automatski rad	'Turbo' tipka	Prikaz sata
										
Kompaktan dizajn	Samodijagnoza	Automatsko pokretanje	Zaključavanje tipki	Mono i multi kompatibilnost	Globalno Wi-Fi upravljanje	R410A				